

EXHIBIT M

EXHIBIT 9

(12) **United States Patent**
Gallagher et al.

(10) **Patent No.:** **US 9,825,826 B2**
(45) **Date of Patent:** ***Nov. 21, 2017**

(54) **METHOD AND APPARATUS FOR
SPECTRUM MONITORING**

(71) Applicant: **MaxLinear, Inc.**, Carlsbad, CA (US)

(72) Inventors: **Timothy Gallagher**, Encinitas, CA
(US); **Patrick Tierney**, Solana Beach,
CA (US); **Jun Huang**, San Diego, CA
(US)

(73) Assignee: **Maxlinear, Inc.**, Carlsbad, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.
This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/948,947**

(22) Filed: **Nov. 23, 2015**

(65) **Prior Publication Data**

US 2016/0087865 A1 Mar. 24, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/341,880, filed on
Jul. 28, 2014, now Pat. No. 9,203,653, which is a
continuation of application No. 13/607,916, filed on
Sep. 10, 2012, now Pat. No. 8,792,008.

(60) Provisional application No. 61/532,098, filed on Sep.
8, 2011.

(51) **Int. Cl.**

H04N 17/00 (2006.01)
H04L 12/26 (2006.01)
H04L 12/66 (2006.01)
H04B 17/309 (2015.01)

(52) **U.S. Cl.**

CPC **H04L 43/08** (2013.01); **H04B 17/309**
(2015.01); **H04L 12/66** (2013.01); **H04N**
17/00 (2013.01)

(58) **Field of Classification Search**

CPC H04N 17/00
USPC 348/192, 193, 180
See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,038,435 A 3/2000 Zhang
7,162,731 B2 * 1/2007 Reidhead H04L 1/24
348/180
7,418,240 B2 * 8/2008 Hsu H04L 1/0003
370/252

(Continued)

Primary Examiner — Paulos M Natnael


(74) *Attorney, Agent, or Firm* — McAndrews, Held &
Malloy, Ltd.

(57)

ABSTRACT

A receiver is configured to be coupled to a television and
data service provider headend via a hybrid fiber coaxial
(HFC) network. The receiver comprises front-end circuitry
operable to receive a signal that carries a plurality of
television and/or data channels, and digitize the received
signal to generate a digitized signal. The receiver comprises
channelizer circuitry operable to select a first portion of the
digitized signal, and select a second portion of the digitized
signal. The receiver comprises processing circuitry operable
to process the selected second portion of the digitized signal
to recover information carried in the plurality of channels.
The receiver comprises monitoring circuitry operable to
analyze the selected first portion of the digitized signal to
measure a characteristic of the received signal; and control
the transmission of network management messages back to
the headend based on the measured characteristic of the
received signal.

18 Claims, 7 Drawing Sheets



US 9,825,826 B2

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

8,161,388	B2 *	4/2012	Rodriguez	G06F 3/14 348/125
8,611,483	B2 *	12/2013	Zhu	H04L 7/0334 341/122
8,792,008	B2 *	7/2014	Gallagher	H04L 43/08 348/192
9,026,118	B2 *	5/2015	Ling	H04W 72/044 370/316
9,203,653	B2 *	12/2015	Gallagher	H04L 43/08
9,320,019	B2 *	4/2016	Gallagher	H04W 72/04
9,332,214	B2 *	5/2016	Ideura	H04N 5/775
2005/0152557	A1 *	7/2005	Sasaki	H04S 7/302 381/58
2010/0171659	A1 *	7/2010	Waters	H04B 17/24 342/357.74
2011/0235758	A1 *	9/2011	Khoini-Poorfard	H03G 3/001 375/345
2012/0163290	A1	6/2012	Krafft et al.		

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B

158B




FIG. 3




FIG. 4

US 9,825,826 B2

1

METHOD AND APPARATUS FOR SPECTRUM MONITORING

PRIORITY CLAIM

This patent application is a continuation of U.S. patent application Ser. No. 14/341,880 filed on Jul. 28, 2014 now patented as U.S. Pat. No. 9,203,653, which is a continuation of U.S. patent application Ser. No. 13/607,916 filed on Sep. 10, 2012 now patented as U.S. Pat. No. 8,792,008, which also makes reference to, claims priority to and claims benefit from U.S. Provisional Patent Application Ser. No. 61/532,098 filed on Sep. 8, 2011. Each of the above referenced documents is hereby incorporated herein by reference in its entirety.

INCORPORATION BY REFERENCE

This patent application also makes reference to: U.S. patent application Ser. No. 13/336,451 titled "Method and Apparatus for Broadband Data Conversion," filed on Dec. 23, 2011, and published as U.S. Patent Application Publication No. 2012/0163518;

U.S. patent application Ser. No. 13/485,003 titled "Multi-layer Time-Interleaved Analog-to-Digital Converter (ADC)," filed on May 31, 2012 and now patented as U.S. Pat. No. 8,611,483; and

U.S. patent application Ser. No. 13/588,769 titled "Multi-Standard Coverage Map Generation," filed on Aug. 17, 2012, and now patented as U.S. Pat. No. 9,026,118.

Each of the above referenced documents applications is hereby incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

Certain embodiments of the invention relate to signal processing. More specifically, certain embodiments of the invention relate to a method and system for spectrum monitoring.

BACKGROUND OF THE INVENTION

Network-based services can become unacceptable if network parameters fall outside of those for which receivers in the network were designed. For example, in a cable television system there are specifications for the number of channels on the plant, the types of channels, the signal levels of those channels and the impairments that can be on the plant that would affect the performance of the receiver. If some or all of these parameters deviate outside acceptable bounds, the user may experience unacceptable performance. Conventional methods and apparatuses for monitoring network parameters are too costly and impractical for use in customer-premises equipment (CPE).

Further limitations and disadvantages of conventional and traditional approaches will become apparent to one of skill in the art, through comparison of such systems with some aspects of the present invention as set forth in the remainder of the present application with reference to the drawings.

BRIEF SUMMARY OF THE INVENTION

A system and/or method is provided for spectrum monitoring, substantially as shown in and/or described in connection with at least one of the figures, as set forth more completely in the claims.

2

These and other advantages, aspects and novel features of the present invention, as well as details of an illustrated embodiment thereof, will be more fully understood from the following description and drawings.

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWINGS

FIG. 1A depicts an example cable system in accordance with an example embodiment of the invention.

FIG. 1B depicts an example receiver operable to perform spectrum monitoring in accordance with an example embodiment of the invention.

FIG. 1C depicts an example satellite system in accordance with an example embodiment of the invention.

FIG. 2A depicts an example RF front-end of a receiver operable to perform spectrum monitoring in accordance with an example embodiment of the invention.

FIG. 2B depicts another example RF front-end of a receiver operable to perform spectrum monitoring in accordance with an example embodiment of the invention.

FIG. 3 depicts an example channelizer which may be utilized for performing spectrum monitoring in accordance with an example embodiment of the invention.

FIG. 4 is a flow chart illustrating example steps for spectrum monitoring in accordance with an example embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

As utilized herein the terms "circuits" and "circuitry" refer to physical electronic components (i.e. hardware) and any software and/or firmware ("code") which may configure the hardware, be executed by the hardware, and or otherwise be associated with the hardware. As utilized herein, "and/or" means any one or more of the items in the list joined by "and/or". For example, "x and/or y" means any element of the three-element set { (x), (y), (x, y) }. Similarly, "x, y, and/or z" means any element of the seven-element set { (x), (y), (z), (x, y), (x, z), (y, z), (x, y, z) }. As utilized herein, the terms "block" and "module" refer to functions than can be implemented in hardware, software, firmware, or any combination of one or more thereof.

FIG. 1A depicts an example communication system in accordance with an example embodiment of the invention. Shown in FIG. 1 is a terrestrial television antenna 102, a satellite dish 104, an Internet Protocol (IP) network 106, a headend 108, a wide area network (e.g., hybrid fiber-coaxial (HFC) network) 118, a gateways 120a and 120b, end systems 126a and 126b (e.g., computers), and end systems 128a and 128b. The headend 108 comprises a switch 110, a video modulator 112, a cable modem termination system (CMTS) 114, and a splitter/combiner 116.

For downstream traffic, the headend 108 may receive television signals via the antenna 102 and the satellite dish 104, and may receive data via the IP network 106. The switch 110 may convey the television signals to the video modulator 112 and the data to the CMTS 114. The video modulator 112 may modulate the received television signals onto a carrier. The CMTS 114 may modulate the received data onto a carrier. The splitter/combiner 116 may combine the outputs of the video modulator 112 and the CMTS 114 resulting in a frequency division multiplexed (FDM) signal comprising one or more television channels and/or one or more DOCSIS channels. The FDM signal may be onto the wide area network (WAN) 118 for distribution to customer

US 9,825,826 B2

3

premise equipment (CPE). Each of the gateways **120a** and **120b** may comprise a receive module **150** operable to process the received FDM signal as described below.

In an example embodiment, each of the gateways **120a** and **120b** may be operable to transmit, via a module **152**, messages to the CMTS **114**. For such upstream data, the gateways **120a** and **120b** may modulate messages (e.g., network management/maintenance messages) onto one or more carriers for transmission via the WAN **118**. The splitter/combiner **116** may then convey the message to the CMTS **114**. The CMTS **114** may process the messages and, in an example embodiment, adjust transmission parameters (e.g., modulation parameters, transmit power, frequency offsets, etc.) and/or perform other maintenance/management based on the received messages.

FIG. 1B depicts an example receiver operable to perform spectrum monitoring in accordance with an example embodiment of the invention. Shown in FIG. 1B is a receiver circuit **100** comprising an RF receive front-end module **158**, a channelizer module **102**, a monitoring module **154**, and a data processing module **156**.

The RF receive front-end **158** may be operable to process a received RF signal *S* to generate a digital signal *D*. The signal *S* may be the result of a plurality of television and/or DOCSIS channels being frequency division multiplexed into a single signal. The signal *S* may occupy a frequency band from F_{lo} to F_{hi} . The RF front-end **158** may, for example, amplify, down-convert, filter, and/or digitize the received signal *S* to generate the digital signal *D*. Example embodiments of the RF front-end are depicted in FIGS. 2A and 2B.

The channelizer **102** may be operable to select $J+1$ bands (represented as C_1 - C_{J+1}) of the signal *S* and output each of the selected bands to the monitoring module **154** and/or the data processing module **156**, where J is an integer greater than 1. An example embodiment of the channelizer **102** is depicted in FIG. 3. Each band C_j may, for example, correspond to the frequency band of one or more television channels. For example, each band C_j may be an integer multiple of 6 MHz (U.S.) or 8 MHz (EU).

In an example embodiment, the channelizer **102** may be implemented entirely in the digital domain and the channelization may be achieved via one or more digital filtering algorithms and/or other digital signal processing algorithms.

The monitoring module **154** may be operable to analyze the band C_{J+1} that it receives from the channelizer **102** to measure/determine characteristics such as, for example, signal power level vs. frequency, delay vs. frequency, phase shift vs. frequency, type and/or amount of modulation, code rate, interference levels, signal to noise ratio, a transfer function of the channel of over which the signal was received, an impulse response of the channel over which the signal was received, and/or any other characteristic that may help assess characteristics of the channel over which the signal was received, assess characteristics of the transmitter that sent the signal and/or any otherwise be pertinent to performance of the communication system. The monitoring module may also be operable to generate one or more control signals **160** for configuring the channelizer **102** and/or for configuring the RF front-end **158**. Additionally or alternatively, the control signal(s) **160** output by the monitoring module **154** may control the transmission of network management/maintenance messages by the device **150**. Such message may comprise, for example, network status updates indicating whether one or more communication parameters of one or more received television or DOCSIS channels are outside acceptable bounds, and/or conveying measured/

4

determined characteristics back to a source of the received signal (e.g., back to a cable headend). In an example embodiment, the monitoring module **174** may be operable to demodulate signals for measuring one or more characteristics such as signal-to-noise ratio, code rate.

The data processing module **156** may be operable to process the bands C_1 - C_J conveyed to it by the channelizer **102** to recover data present in one or more television channels present in those bands of the signal *S*. The data processing module **156** may, for example, perform synchronization, equalization, and decoding. The data processing module **156** may output processed data (e.g., MPEG transport stream packets and/or Internet Protocol packets) to end systems **126**, perhaps via an interface such as an HDMI interface and/or an Ethernet interface (not shown). The data processing module **156** may also be operable to generate one or more control signals **162** for configuring the channelizer **102** and/or the receive front-end **158**.

The parallel arrangement of the monitoring module **154** and data processing module **156** may enable determination of signal and/or channel characteristics without having to interrupt service to user equipment **126** and **128**.

In an example embodiment, the signal *S* may be a cable television signal with $F_{lo} \approx 55$ MHz, $F_{hi} \approx 1002$ MHz. In an example embodiment, the signal *S* may be a MoCA signal with $F_{lo} \approx 1150$ MHz and $F_{hi} \approx 2100$ MHz. These numbers are purely for illustration and not intended to be limiting.

In an example embodiment, the signal *S* may be a satellite television signal such as may be at the input of a LNB, at the output of a LNB, or at the input of an indoor unit (e.g., set-top box). In such an embodiment, the front-end **158**, channelizer **152**, data processing module **154**, and/or monitoring module **154** may reside in the indoor unit (e.g., set-top box), outdoor unit (e.g., satellite dish or accompanying components), and/or may be distributed among the indoor unit and outdoor unit of a satellite installation residing at a customer premises. An example of such an embodiment is shown in FIG. 1C.

In operation of such an example embodiment, the signal *S* may be amplified, possibly downconverted, and digitized by the RF front-end **158** to generate the signal *D*. The channelizer **102** may then select J bands of the signal *D* for output to the data processing module **156**. Each of the selected bands C_1 - C_J may, for example, comprise one or more of the cable television channels and/or one or more of the DOCSIS channels that make up the signal *S*. The data processing module **156** may provide one or more control signals to determine which portion of the signal *D* is selected for each of the bands C_1 - C_J . The selection may be based, for example, on which television channels are being consumed by end systems **128** and/or whether DOCSIS data is being consumed by end systems **126**. The channelizer **102** may also select one band, represented as band C_{J+1} , to be output to the monitoring module **154**. Band C_{J+1} may comprise any portion or portions (including the entire bandwidth from F_{lo} to F_{hi}) of the signal *D*. Which portion of the signal *S* is selected as band C_{J+1} may, for example, be configured by the monitoring module **154**. The data processing module **156** may process one or more of bands C_1 - C_J to recover data on one or more channels (e.g., television and/or DOCSIS channels) present in those bands while the monitoring module **154** may concurrently process band C_{J+1} to measure/determine characteristics of all or a portion of the signal *S* between f_{lo} and f_{hi} .

FIG. 1C depicts an example satellite system in accordance with an example embodiment of the invention. Shown in FIG. 1C is a satellite dish assembly **172**, and a gateway **196**.

US 9,825,826 B2

5

The subassembly **174** comprises a feed horn **182**, an LNB **194**, the front-end **158**, the channelizer **152**, the monitoring module **154**, and the data processing module **156**. The various modules of the subassembly **174** may reside in one or more housings, on one or more printed circuit boards, and/or one or more integrated circuits (e.g., one or more silicon dice). In another example embodiment, the monitoring module **154** and/or the data processing module **156** may reside in the gateway **196**.

In the example embodiment depicted, the satellite dish assembly **172** comprises a parabolic reflector **176** and a subassembly **174** mounted (e.g., bolted or welded) to a support structure **178** which, in turn, comprises a boom **190** and attaches (e.g., via bolts) to the premises **180** (e.g., to the roof). In another example embodiment, all or a portion of the modules **152**, **154**, and/or **156** may be mounted to the premises **180** separate from the satellite dish (e.g., connected via wired and/or wireless connections), but may still be part of the "outdoor unit."

The gateway **196** may receive data from the satellite dish assembly **172** (via cable(s) **184**). The gateway and may transmit data onto and receive data from the WAN **192** (via broadband connection **188**). The gateway **196** may transmit data to and receive data from user equipment **128** and **126** (via one or more connections **186**).

FIG. 2A depicts an example RF front-end of a receiver operable to perform spectrum monitoring in accordance with an example embodiment of the invention. The RF front-end **158A** shown in FIG. 2A comprises a variable gain amplifier **202**, and receive chains **204₁-204_L**, where **L** is an integer greater than or equal to 1. Each receive chains **204₁** may comprise an amplifier module **210₁**, a mixer module **212₁**, a filter module **214₁**, and an analog-to-digital converter (ADC) module **216₁**, where **1** is an integer between 1 and **L**.

Each amplifier **210₁** may be operable to amplify a band 1 of the signal **S**. Each mixer **212₁** may be operable to mix a band 1 of the signal **S** with a local oscillator signal (not shown) to downconvert the band 1 to a lower frequency. Each filter module **214₁** may be operable to bandpass filter the band 1 to remove/attenuate frequencies outside band 1. Each ADC **216** may be operable to convert the band 1 of the analog signal **S** to a corresponding digital representation. Operation of the RF front-end **158** and/or processing of signals generated by the front-end **158**, may, for example, be as described in U.S. patent application Ser. No. 13/336,451 entitled "Method and Apparatus for Broadband Data Conversion" which is incorporated by reference herein, as set forth above.

In an example embodiment, the front-end **158A** may reside in a cable gateway such as the cable gateway **120** described above. In an example embodiment, the front-end **158A** may reside in satellite gateway/set-top box and/or in an outdoor unit of a satellite reception assembly (e.g., collocated on-chip or on-PCB with a satellite low-noise block downconverter (LNB)).

FIG. 2B depicts another example RF front-end of a receiver operable to perform spectrum monitoring in accordance with an example embodiment of the invention. The RF front-end **158B** shown in FIG. 2B comprises a variable gain amplifier **252**, a filter **254**, and an ADC **256**. Functions performed by the RF front-end **158B** may be referred to as "full-spectrum capture" (or "FSC").

In the front-end **158B**, the entire bandwidth, from F_{lo} to F_{hi} , of signal **S** may be amplified by the amplifier **252** to generate **S'**. The amplified signal **S'** may be then filtered by the filter **254** to remove undesired signals outside of F_{lo} to F_{hi} and generate signal **S''**. The signal **S''**, from F_{lo} to F_{hi} ,

6

may then be digitized by the ADC **256** to generate signal **D**. In an example embodiment, the ADC may be as described in U.S. patent application Ser. No. 13/485,003 entitled "Multi-layer Time-Interleaved Analog-to-Digital Converter (ADC)," which is incorporated by reference herein, as set forth above.

In an example embodiment, the ADC **256** may be capable of digitizing a signal **S** wherein F_{lo} to F_{hi} is 1 GHz or higher. Accordingly, for cable television/DOCSIS, the ADC **256** may be operable to digitize the entire cable downstream (e.g., from ~55 MHz to ~1002 MHz). Similarly, for satellite television, the ADC **256** may be operable to digitize the received signal at the input of the LNB, and/or the down-converted signal (e.g., from ~1 GHz to ~2 GHz) at the output by an LNB.

FIG. 3 depicts an example channelizer which may be utilized for performing spectrum monitoring in accordance with an example embodiment of the invention. Band selection filters **302₁-302_J** of the channelizer **102** may each process the signal **D** to recover a corresponding one of the **J** selected bands of the signal **D**, and output the band on a corresponding one of the ports **304₁** to **304_J**. A band selection filter **302_{J+1}** of the channelizer **102** may process the signal **D** to recover band C_{J+1} from the signal **D**, and output band C_{J+1} on the port **304_{J+1}**. Which band or bands are selected by the filter **302_{J+1}** may be configured based on one or more control signals input to the channelizer **102**. For example, the value of a parameter **k** may determine the center frequency of the portion of signal **D** that is to be selected as C_{J+1} by the filter **302_{J+1}**, and the value of Δ may determine the bandwidth of the portion of this signal **D** that is selected as band C_{J+1} for output on the port **304_{J+1}**. In this manner, all of the signal **D** between F_{lo} and F_{hi} , or any portion or portions of the signal **D**, may be selected for output on the port **304_{J+1}**.

FIG. 4 is a flow chart illustrating example steps for spectrum monitoring in accordance with an example embodiment of the invention. After start step **402**, in step **404**, the receiver circuit **100** may receive a frequency division multiplexed (FDM) signal comprising one or more channels (e.g., satellite television channels, cable television channels, and/or DOCSIS channels) occupying a frequency band between F_{lo} and F_{hi} . In step **406**, the received FDM signal is digitized across the full band from F_{lo} to F_{hi} . In step **408**, the digitized signal is channelized into one or more bands. In step **410**, a first one or more of the bands are conveyed to a data processing module. In step **412** a second one or more of the bands are output to a monitoring module. In step **414**, the data processing module processes one or more of the first one or more bands to recover data on those bands while the monitoring module concurrently processes the second one or more bands to determine characteristics of all or a portion of the frequency band from F_{lo} to F_{hi} .

Other embodiments of the invention may provide a non-transitory computer readable medium and/or storage medium, and/or a non-transitory machine readable medium and/or storage medium, having stored thereon, a machine code and/or a computer program having at least one code section executable by a machine and/or a computer, thereby causing the machine and/or computer to perform the steps as described herein for spectrum monitoring.

Accordingly, the present invention may be realized in hardware, software, or a combination of hardware and software. The present invention may be realized in a centralized fashion in at least one computing system, or in a distributed fashion where different elements are spread across several interconnected computing systems. Any kind

US 9,825,826 B2

7

of computing system or other apparatus adapted for carrying out the methods described herein is suited. A typical combination of hardware and software may be a general-purpose computing system with a program or other code that, when being loaded and executed, controls the computing system such that it carries out the methods described herein. Another typical implementation may comprise an application specific integrated circuit or chip.

The present invention may also be embedded in a computer program product, which comprises all the features enabling the implementation of the methods described herein, and which when loaded in a computer system is able to carry out these methods. Computer program in the present context means any expression, in any language, code or notation, of a set of instructions intended to cause a system having an information processing capability to perform a particular function either directly or after either or both of the following: a) conversion to another language, code or notation; b) reproduction in a different material form.

While the present invention has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the present invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the present invention without departing from its scope. Therefore, it is intended that the present invention not be limited to the particular embodiment disclosed, but that the present invention will include all embodiments falling within the scope of the appended claims.

What is claimed is:

1. A method comprising:
performing by one or more circuits of a receiver coupled to a television and data service provider headend via a hybrid fiber coaxial (HFC) network:
receiving, via said HFC network, a signal that carries a plurality of channels, wherein said channels comprise one or both of television channels and data channels;
digitizing said received signal to generate a digitized signal;
selecting a first portion of said digitized signal;
selecting a second portion of said digitized signal;
processing said selected second portion of said digitized signal to recover information carried in said plurality of channels;
analyzing said selected first portion of said digitized signal to measure a characteristic of said received signal; and
controlling the transmission of network management messages back to said headend based on said measured characteristic of said received signal, wherein said measured characteristic is different than said network management messages.
2. The method of claim 1, wherein said network management messages indicate whether a parameter is outside of acceptable bounds.
3. The method of claim 2, wherein said parameter is a modulation parameter of said received signal.

8

4. The method of claim 2, wherein said parameter is a transmit power of said received signal.

5. The method of claim 2, wherein said parameter is a frequency offset of said received signal.

6. The method of claim 1, wherein said characteristic is signal power vs. frequency.

7. The method of claim 1, wherein said characteristics is signal phase vs. frequency.

8. The method of claim 1, wherein said characteristic is one of: signal-to-noise ratio, peak-to-average ratio, noise levels, bit error rate, and symbol error rate.

9. The method of claim 1, configuring, by said one or more circuits, a bandwidth and/or center frequency of said selected first portion of said digitized signal.

10. A system comprising:

a receiver configured to be coupled to a television and data service provider headend via a hybrid fiber coaxial (HFC) network, the receiver comprising:

front-end circuitry operable to:

receive a signal that carries a plurality of channels, wherein said channels comprise one or both of television channels and data channels; and
digitize said received signal to generate a digitized signal;

channelizer circuitry operable to:

select a first portion of said digitized signal; and
select a second portion of said digitized signal;
processing circuitry operable to process said selected second portion of said digitized signal to recover information carried in said plurality of channels;

monitoring circuitry operable to:

analyze said selected first portion of said digitized signal to measure a characteristic of said received signal; and

control the transmission of network management messages back to said headend based on said measured characteristic of said received signal, wherein said measured characteristic is different than said network management messages.

11. The system of claim 10, wherein said network management messages indicate whether a parameter is outside of acceptable bounds.

12. The system of claim 11, wherein said parameter is a modulation parameter of said received signal.

13. The system of claim 11, wherein said parameter is a transmit power of said received signal.

14. The system of claim 11, wherein said parameter is a frequency offset of said received signal.

15. The method of claim 1, wherein said characteristic is signal power vs. frequency.

16. The method of claim 1, wherein said characteristics is signal phase vs. frequency.

17. The system of claim 10, wherein said characteristic is one of: signal-to-noise ratio, peak-to-average ratio, noise levels, bit error rate, and symbol error rate.

18. The system of claim 10, comprising configuring, by said monitoring circuitry during operation of said one or more circuits, a bandwidth and/or center frequency of said selected first portion of said digitized signal.

* * * * *